

90 cm 5-burner electric double oven Master Series




MAS905MFEDXE

The double-oven range cooker give great versatility and style to your kitchen. The main oven electric oven has 11 functions, from convection, baking and grilling to warming. The useful auxiliary oven has five modes. Triple-glass doors minimise heat loss.

The hob has five versatile gas burners in aluminium including a dual-ring power burner giving anything from a delicate low simmer to full power.

Matching range hood and backsplash available.

Products and packaging are 99% recyclable 

Colours shown will vary depending on your screen settings and resolution. Contact your dealer for further advice.

Specifications

Features

Worktop

Size	90 cm
Cooking zones	5
Gas zones	5
Worktop type	gas
Worktop design	stainless steel squared
Worktop controls	knobs
Knobs	black soft touch
Burner type	aluminium
Pan supports	cast iron
Continous grating	yes
Flame failure device	yes
One-hand ignition	yes
Upstand	yes
Wok adapter	yes
Simmer ring	yes

Cooking zones

Dual wok	0.48 kW - 1 kW
Semi-rapid	0.60 kW - 1.75 kW (2)
Auxiliary	0.48 kW - 1 kW (1)

Oven cavity

Oven configuration	double
Oven fuel	electric
Main oven type	electric multifunction
Main oven grill type	electric
Main oven functions	bake / bottom bake / convection / convection bake / convection grill / defrosting / dehydrate / fast preheat / grill / oven light / pizza / upper bake
Main oven volume	69 l
Main oven convection system	single with heating element

Main oven energy rating	A
Auxiliary oven type	electric conventional
Auxiliary oven grill type	electric
Auxiliary oven functions	bake / bottom bake / grill / oven light / upper bake
Auxiliary oven volume	38 l
Auxiliary oven energy rating	A+
Second oven volume	38 l
Oven controls	knobs
Inner oven door	triple
Removable inner glass	yes
Cooling fan	yes
Oven levels	4
Oven door closing	standard
Sliding shelves	2 standard
Wire-shelves	3 chromed
Tray	2 enamelled
Grill trivet for tray	yes
Oven lights	double
Bottom	
Storage compartment	flap
Legs	stainless steel
Technical specifications	
Electrical requirements	220/240 V - 50/60 Hz - 17.90 A
Nominal power	4100 W
Recommended connection	2 x 10A alt 3 x 10A (or higher)

Dimensions

