

90 cm induction top electric double oven Professional Series




PRO905IMFEDXE

The double-oven range cooker give great versatility and style to your kitchen. The main oven electric oven has 11 functions, from convection, baking and grilling to warming.

The useful auxiliary oven has six modes. Triple-glass doors minimise heat loss.

The hob has an induction top with five heating zones, including booster feature, pot detection and residual heat indicator for each zone.

Matching range hood and backsplash available.

Products and packaging are 99% recyclable 

Specifications

Features

Worktop

Size 90 cm

Cooking zones 5

Number of induction zones 5

Worktop type induction

Worktop controls knobs

Knobs metal coated

Upstand yes

Cooking zones

Induction front right (Ø 160.00 mm) 1100 W - 1400 W

Induction front left (Ø 160.00 mm) 1100 W - 1400 W

Induction back right (Ø 200.00 mm) 2300 W - 3000 W

Induction back left (Ø 200.00 mm) 1400 W - 2000 W

Induction center (Ø 230.00 mm) 2300 W - 3000 W

Oven cavity

Oven configuration double

Oven fuel electric

Main oven type electric multifunction

Main oven grill type electric

Main oven functions bake / bottom bake / convection / convection bake / convection grill / defrosting / dehydrate / fast preheat / grill / oven light / pizza / upper bake

Main oven volume 69 l

Main oven convection system single with heating element

Main oven energy rating A

Auxiliary oven type electric conventional

Auxiliary oven grill type electric

Auxiliary oven functions bake / bottom bake / grill / oven light / turnspit / upper bake

Auxiliary oven volume 38 l

Auxiliary oven energy rating A+

Second oven volume	38 l
Oven controls	knobs
Inner oven door	triple
Removable inner glass	yes
Cooling fan	yes
Oven levels	4
Food probe	yes
Oven door closing	anti-slam system
Wire-shelves	3chromed
Tray	2 enamelled
Grill trivet for tray	yes
Oven lights	single
Bottom	
Storage compartment	drawer
Legs	stainless steel
Technical specifications	
Voltage and frequency	220/240 V - 50/60 Hz - 50 A
Absorbed power (W)	11500 W
Recommended connection	3 x 20A (or higher)

Dimensions

